

NASA TECH BRIEF

NASA Pasadena Office



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Diffused Guides for Distributed-Feedback Lasers

In optical communication systems currently under development, laser beams are conducted through fiber-optics lines (light pipes). To reduce coupling losses between the laser source and the light pipe, specially-configured fiber-optic transmission line is used. This line is structured to amplify the light signal, forming in effect a distributed-feedback laser. As the beam progresses through the line, the periodically varying index of refraction scatters the beam. Thus, a chain of resonant cavities is formed without conventional mirror optics. One such pipe, incorporating periodically-spaced micromechanical notches, has been described in NASA Tech Brief B75-10127 (NPO-13531).

An alternate procedure is to use a diffused optical waveguide. The proposed waveguide is a hollow cylindrical pipe. Inside, the pipe forms a diffused channel, i.e., gas or metal molecules are infused into the channel walls by heating or other conventional means. Thus the channel surface is corrugated, forming periodic cross sections along the entire length. As the light is guided along the channel, it is scattered at the periodic infusions, resulting in distributed feedback. The high index of refraction at the wall causes the pipe to act as a waveguide and eliminates the losses by radiation.

The described configuration is particularly suited for capillary gas lasers. A similar half-channel (semicylindrical) guide can be constructed as an integrated optics element. Theoretical calculations have shown the feasibility of such light pipes operating in TE modes. These types of guides are relatively simple to fabricate.

Note:

Requests for further information may be directed to:

Technology Utilization Officer
NASA Pasadena Office
4800 Oak Grove Drive
Pasadena, California 91103
Reference: TSP75-10206

Patent status:

This invention is owned by NASA, and a patent application has been filed. Inquiries concerning nonexclusive or exclusive license for its commercial development should be addressed to:

Patent Counsel
NASA Pasadena Office
4800 Oak Grove Drive
Pasadena, California 91103

Source: Charles Elachi of
Caltech/JPL
(NPO-13544)

Category: 03 (Physical Sciences)